

Headroom Clearance Dimensions

Dimensions A and B

C275 Slats

Max. Wall Opening Height ^a	C275 Slat					
	Thru 14'-0" Wide		Thru 20'-0" Wide		Thru 24'-0" Wide	
	A	B**	A	B**	A	B**
Thru 8'0"	19 1/2"	21 5/8"	21 1/2"	23 5/8"	21 1/2"	23 5/8"
Thru 10'0"	19 1/2"	21 5/8"	21 1/2"	23 5/8"	21 1/2"	23 5/8"
Thru 11'0"	19 1/2"	21 5/8"	21 1/2"	23 5/8"	23 1/2"	25 5/8"
Thru 12'0"	21 1/2"	23 5/8"	21 1/2"	23 5/8"	23 1/2"	25 5/8"
Thru 13'0"	21 1/2"	23 5/8"	21 1/2"	23 5/8"	23 1/2"	25 5/8"
Thru 14'0"	21 1/2"	23 5/8"	21 1/2"	23 5/8"	23 1/2"	25 5/8"
Thru 16'0"	21 1/2"	23 5/8"	21 1/2"	23 5/8"	25 1/2"	27 5/8"
Thru 18'0"	21 1/2"	23 5/8"	25 1/2"	27 5/8"	■	■
Thru 19'0"	23 1/2"	25 5/8"	25 1/2"	27 5/8"	■	■
Thru 21'0"	23 1/2"	25 5/8"	27 1/2"	29 5/8"	■	■
Thru 24'0"	25 1/2"	27 5/8"	■	■	■	■

^aHeight limit for non-masonry jambs is 12'0".

**Add 2" for electric operation.

■ Consult factory