

Headroom Clearance Dimensions

Dimensions A and B

C265 Slats

Max. Wall Opening Height ^a	F265 Slat					
	Thru 14'-0" Wide		Thru 20'-0" Wide		Thru 24'-0" Wide	
	A	B ^{**}	A	B ^{**}	A	B ^{**}
Thru 8'0"	21 1/2	23 5/8	21 1/2	23 5/8	21 1/2	23 5/8
Thru 10'0"	21 1/2	23 5/8	21 1/2	23 5/8	21 1/2	23 5/8
Thru 11'0"	21 1/2	23 5/8	21 1/2	23 5/8	23 1/2	25 5/8
Thru 12'0"	21 1/2	23 5/8	21 1/2	23 5/8	23 1/2	25 5/8
Thru 13'0"	21 1/2	23 5/8	21 1/2	23 5/8	23 1/2	25 5/8
Thru 14'0"	21 1/2	23 5/8	21 1/2	23 5/8	23 1/2	25 5/8
Thru 16'0"	23 1/2	25 5/8	23 1/2	25 5/8	25 1/2	27 5/8
Thru 18'0"	23 1/2	25 5/8	23 1/2	25 5/8	■	■
Thru 19'0"	23 1/2	25 5/8	25 1/2	27 5/8	■	■
Thru 21'0"	23 1/2	25 5/8	27 1/2	29 5/8	■	■
Thru 24'0"	■	■	■	■	■	■

^aHeight limit for non-masonry jams is 12'0".

^{**}Add 2" for electric operation.

■ Consult factory