



Commercial Operator

Selection Guide

Sectional Doors

Maximum Door Size
(in sq. ft.)

| Model Operator | HP | UL Listed | Type Mount | Max Door Wt. Lbs | Thermacore | | | | | | Aluminum | |
|----------------|-----|-----------|------------|------------------|------------|-----|-----|-----|-----|-----|----------|-----|
| | | | | | 591 | 592 | 593 | 594 | 595 | 598 | 511 | 520 |
| ArmDr | 1/2 | YES | TSC | 1500 | 490 | 448 | 326 | 326 | 406 | 200 | 326 | 506 |
| MD | 1/2 | YES | TS | 620 | 262 | 262 | 262 | 292 | 200 | 200 | 200 | 230 |
| SEL | 1/3 | YES | TS | 650 | 294 | 262 | 278 | 292 | 200 | 200 | 230 | 230 |
| JST | 1/3 | YES | TSC | 770 | 330 | 330 | 310 | 310 | 262 | 200 | 278 | 294 |
| L(20:1) | 1/3 | YES | T | 770 | 330 | 330 | 310 | 310 | 262 | 200 | 278 | 294 |
| L(40:1) | 1/3 | YES | SC | 960 | 366 | 366 | 326 | 326 | 330 | 200 | 326 | 366 |
| SEL | 1/2 | YES | TS | 940 | 366 | 366 | 326 | 326 | 330 | 200 | 326 | 330 |
| JST | 1/2 | YES | TS | 1100 | 406 | 406 | 326 | 326 | 366 | 200 | 326 | 406 |
| L (20:1) | 1/2 | YES | T | 1100 | 406 | 406 | 326 | 326 | 366 | 200 | 326 | 406 |
| L (40:1) | 1/2 | YES | SC | 1310 | 490 | 448 | 326 | 326 | 406 | 200 | 326 | 466 |
| JST | 3/4 | YES | TSC | 1450 | 490 | 448 | 326 | 326 | 406 | 200 | 326 | 506 |
| L(20:1) | 3/4 | YES | T | 1450 | 490 | 448 | 326 | 326 | 406 | 200 | 326 | 506 |
| L(40:1) | 3/4 | YES | SC | 1650 | 536 | 536 | 325 | 326 | 448 | 200 | 326 | 526 |
| SDB L.D. | 1 | YES | SC | 1980 | 632 | 584 | 326 | 326 | 536 | 200 | 326 | 526 |
| SDB H.D. | 1 | YES | SC | 2420 | 792 | 736 | 326 | 326 | 632 | 200 | 326 | 526 |
| SDB H.D. | 2 | YES | SC | 3080 | 970 | 850 | 326 | 326 | 792 | 200 | 326 | 526 |

Maximum Door Size
(in sq. ft.)

| Model Operator | HP | UL Listed | Type Mount | Max Door Wt. Lbs | Steel Insulated & Non-Insulated | | | | | | | |
|----------------|-----|-----------|------------|------------------|---------------------------------|-----|-----|-----|-----|-----|-----|-----|
| | | | | | 416 | 418 | 420 | 422 | 424 | 426 | 430 | 432 |
| ArmDr | 1/2 | YES | TSC | 1500 | 366 | 294 | 448 | 366 | 490 | 406 | 326 | 326 |
| MD | 1/2 | YES | TS | 620 | 148 | 124 | 230 | 174 | 262 | 200 | 294 | 278 |
| SEL | 1/3 | YES | TS | 650 | 174 | 124 | 262 | 200 | 294 | 200 | 294 | 294 |
| JST | 1/3 | YES | TSC | 770 | 200 | 148 | 262 | 200 | 330 | 230 | 326 | 310 |
| L(20:1) | 1/3 | YES | T | 770 | 200 | 148 | 262 | 200 | 330 | 230 | 326 | 310 |
| L(40:1) | 1/3 | YES | SC | 960 | 262 | 200 | 330 | 262 | 406 | 294 | 326 | 326 |
| SEL | 1/2 | YES | TS | 940 | 262 | 200 | 330 | 262 | 406 | 294 | 326 | 326 |
| JST | 1/2 | YES | TS | 1100 | 294 | 230 | 366 | 294 | 448 | 330 | 326 | 326 |
| L (20:1) | 1/2 | YES | T | 1100 | 294 | 230 | 366 | 294 | 448 | 330 | 326 | 326 |
| L (40:1) | 1/2 | YES | SC | 1310 | 330 | 262 | 406 | 330 | 448 | 366 | 326 | 326 |
| JST | 3/4 | YES | TSC | 1450 | 366 | 294 | 448 | 366 | 490 | 406 | 326 | 326 |
| L(20:1) | 3/4 | YES | T | 1450 | 366 | 294 | 448 | 366 | 490 | 406 | 326 | 326 |
| L(40:1) | 3/4 | YES | SC | 1650 | 366 | 294 | 490 | 406 | 536 | 448 | 326 | 326 |
| SDB L.D. | 1 | YES | SC | 1980 | 448 | 366 | 536 | 448 | 632 | 490 | 326 | 326 |
| SDB H.D. | 1 | YES | SC | 2420 | 490 | 406 | 684 | 536 | 792 | 584 | 326 | 326 |
| SDB H.D. | 2 | YES | SC | 3080 | 584 | 490 | 850 | 684 | 850 | 684 | 326 | 326 |

T = Trolley

S = Jackshaft, Side Mount version

C = Jackshaft, Center Mount version

