



Rolling Steel Door - Operator Selection Chart

Maximum Door Size (in sq. ft.)

Model Operator	HP	UL Listed	Rolling Steel Doors										
			600			610/620			615/616	625			
			Coilaway	22ga	20 ga	18 ga	24 ga	24 ga	22 ga	20 ga	18 ga		
RMX	1/2	YES	256 *	203	177	135	267*	125	108	90	75		
RG	1/3	YES	256 *	225	196	150	267	138	120	111	95		
RG	1/2	YES	256 *	292	255	194	267	179	156	145	123		
RG	3/4	YES	256 *	375	327	249	267	230	200	185	158		
RDB	1/2	YES	256 *	403	351	268	267 *	247	215	199	169		
RDB	1	YES	256 *	600	523	399	267 *	367	320	297	252		
RDB	2	YES	256 *	788	948	723	267 *	665	580	538	457		
CDO	1/2	YES	256	125	107	104	267	N/A	N/A	N/A	N/A		

* Operator must be wall mounted.

Maximum Door Size (in sq. ft.)

Model Operator	HP	UL Listed	Rolling Fire Doors/Fire Shutters				Counter Doors	Grilles	
			630/631/634			640/641		650/651/652	670
			22ga	20 ga	18 ga	22 ga	22 ga / Alum	Alum	Steel
RMX	1/2	YES	N/A	N/A	N/A	N/A	ALL *	350	210
RG	1/3	YES	168	196	150	N/A	ALL *	430	120
RG	1/2	YES	168	255	194	N/A	ALL *	450	156
RG	3/4	YES	168	327	249	N/A	ALL *	500	215
RDB	1/2	YES	168	351	268	N/A	ALL *	540	240
RDB	1	YES	168	480	399	N/A	ALL *	700	340
RDB	2	YES	168	480	580	N/A	ALL *	900	740
CDO	1/2	YES	N/A	N/A	N/A	ALL	ALL	238	150

* Operator must be wall mounted, order wall mount kit #111011.0001.S

See Operator Model Page for More Details