



Dimension Charts for EverServe™ Models 610S/620S/625S

Please be advised that the dimensions provided below are approximations based on standard offerings. If options are added or sideroom and headroom clearances are tight on your projects, please be sure to work with the factory for the most accurate data based on your jobs needs.

Models 610S/620S/625S Face of Wall Mounted

| Slat Data | | | | |
|-----------|-------|---------------|-----------|---|
| Model | Slat | Opening Width | Standard | Optional |
| 610S | C187* | Up to 15'4" | 22 ga. | 20,18 ga. or 22,20 ga. ss or .04" (18 ga.) Aluminum |
| 610S | C275 | Up to 20'0" | 22 ga. | 20,18 ga. or 22,20 ga. ss or .05" (16 ga.) Aluminum |
| 610S | F265 | Up to 20'0" | 22 ga. | 20,18 ga. or 22,20 ga. ss or .05" (16 ga.) Aluminum |
| 620S | F265 | Up to 20'0" | 22 ga. | 20,18 ga. or 22,20 ga. ss or .05" (16 ga.) Aluminum Front of slat: 22,20,18 ga. or 22,20 ga. ss or .05" (18 ga.) Aluminum Back of slat: 22 ga. or 22 ga. ss; .025" (22 ga.) |
| 625S | F265i | Up to 20'0" | 24/24 ga. | Aluminum |

*C-187 slat limited to 15'4" in width.
NOTE: 18 ga. C275 and F265 slat profiles on Model 610S are available with full fenestration or partial curtain fenestration

Slats are galvanized and painted steel, stainless steel (ss) or aluminum.

| Slat | R-value | U-value | STC Rating |
|-------|---------|---------|------------|
| F265i | 7.7 | 0.13 | 21 |

Headroom Clearance Dimensions

| Slat | Opening Height | Dimension A | Max Door Opening Width |
|-------|----------------|-------------|------------------------|
| C187 | Thru 8'0" | 14" | 15'4" |
| C187 | Thru 14'0" | 16" | 15'4" |
| C187 | Thru 20'0" | 18" | 15'4" |
| C275 | Thru 5'0" | 14" | 20'0" |
| C275 | Thru 10'0" | 16" | 20'0" |
| C275 | Thru 15'0" | 18" | 20'0" |
| C275 | Thru 20'0" | 20" | 15'0" |
| F265 | Thru 9'0" | 16" | 20'0" |
| F265 | Thru 14'0" | 18" | 20'0" |
| F265 | Thru 20'0" | 20" | 15'0" |
| F265i | Thru 7'0" | 16" | 20'0" |
| F265i | Thru 11'0" | 18" | 20'0" |
| F265i | Thru 16'0" | 20" | 11'0" |
| F265i | Thru 20'0" | 22" | 9'0" |