

**Dimension Charts for Commercial Operators: RMX®**

RMX® Rolling Steel Door Chart (Sq. Ft.)													
Model	HP	UL Listed	Rolling Steel Doors								Counter	Grilles	
			600	610/620			625				650/651/652	670	671
			Coilaway	22GA.	20GA.	18GA.	24GA.	22GA.	20GA.	18GA.	22GA. / Alum	Alum	Steel
RMX	1/2	Yes	256*	203	177	135	125	108	90	75	ALL*	350	210

\* Operator must be wall mounted. For RMX, need to order wall mount kit.

RMX® Sectional Door Chart (Sq. Ft.)																					
Model	HP	UL Listed	Door Series ->	Max. Door Weight (Lbs)	Commercial Steel Insulated & Non-Insulated								Thermacore						Aluminum		
					416	418	420	422	424	426	430	432	591	592	593	594	596	598	599	511	521
					16GA. Flush Steel	16GA. Flush Steel Insulated	20GA. Ribbed Steel	20GA. Ribbed Steel Insulated	24GA. Ribbed Steel	24GA. Ribbed Steel Insulated	Nominal 24GA. Ribbed Steel	Nominal 24GA. Ribbed Steel Insulated	Ribbed Steel 1 5/8"	Ribbed Steel 2"	Ribbed Steel 1 3/8"	Raised Panel Steel 1 3/8"	20GA. Flush Steel 1 5/8"	Ribbed Steel 1"	Flush Steel 2"		
RMX	1/2	Yes	TS	620	160	124	250	174	275	200	294	278	262	262	262	292	200	200	262	200	230

T = Trolley  
 S = Jackshaft, Side Mount  
 Trolley Door Speeds: 11.5" per/sec

Note: Total door weight, and not the square footage, is the critical factor in selecting the proper operator.  
 Square foot measurements are based on "square doors". (Example = 16' x 16')

Note: Doors that require special windloading and wide doors normally require increased strutting (reinforcement). Strutting doors can significantly increase door weight beyond maximum weight shown. Consult factory personnel in these situations.