



Dimension Charts for Rolling Steel Doors: Model 610

Please be advised that the dimensions provided below are approximations based on standard offerings. If options are added or sideroom and headroom clearances are tight on your projects, please be sure to work with the factory for the most accurate data based on your jobs needs.

Model 610 Face-of-Wall Mounted

FOW: Slat Data

Slat	Opening Width	Standard	Optional
C187	Thru 15'4"	22 ga.	20,18 ga. or 22,20 ga. ss
C275	Thru 18'4"	22 ga.	20 ga. or 22,20 ga. ss
C275	Thru 25'4"	20 ga.	16,18 ga. or 20 ga. ss
C275	Thru 30'4"	18 ga.	16 ga.
F265	Thru 18'4"		22, 20,18,16 ga. or 22,20 ga. ss
F265	Thru 25'4"		20, 18,16 ga. or 20 ga. ss
F265	Thru 30'4"		18, 16 ga.

FOW: Headroom Clearance Dimensions

Slat	Opening Height	A Dimension Max Door Opening Widths 15'4"
C187	Thru 6'0"	14"
C187	Thru 11'0"	14"
C187	Thru 18'0"	16"
C187	Thru 21'0"	18"
C187	Thru 30'0"	24"

NOTE: Use *A+5" for electric
Consult factory for doors wider than 30'4"

Slat	Opening Height	A Dimension Max Door Opening Widths		
		20'0"	24'0"	30'0"
C275	Thru 6'0"	14"	14"	18"
C275	Thru 8'0"	16"	16"	18"
C275	Thru 9'0"	16"	18"	20"
C275	Thru 11'0"	16"	18"	20"
C275	Thru 13'0"	18"	18"	20"
C275	Thru 16'0"	18"	20"	22"
C275	Thru 18'0"	20"	22"	24"
C275	Thru 21'0"	22"	22"	24"
C275	Thru 23'0"	22"	24"	24"
C275	Thru 25'0"	24"	24"	26"
C275	Thru 28'0"	24"	24"	26"
C275	Thru 30'0"	26"	26"	28"

NOTE: Use *A+5" for electric
Consult factory for doors wider than 30'4"

Dimension Charts: Model 610

FOW: Headroom Clearance Dimensions

Slat	Opening Height	A Dimension Max Door Opening Widths		
		20'0"	24'0"	30'0"
F265	Thru 6'0"	16"	16"	18"
F265	Thru 8'0"	18"	18"	20"
F265	Thru 9'0"	18"	18"	20"
F265	Thru 11'0"	18"	18"	20"
F265	Thru 13'0"	20"	20"	20"
F265	Thru 16'0"	20"	20"	22"
F265	Thru 18'0"	20"	22"	24"
F265	Thru 21'0"	22"	24"	24"
F265	Thru 23'0"	22"	24"	24"
F265	Thru 25'0"	24"	24"	26"
F265	Thru 28'0"	26"	26"	26"
F265	Thru 30'0"	26"	26"	28"

NOTE: Use *A+5" for electric
Consult factory for doors wider than 30'4"

FOW: Rolled Guide Clearance Dimensions

Slat	Dimensions	Max Door Opening Width 15'4"
C187, F265	G	2 1/2"
C187, F265	M	4 1/2"
C187, F265	D	5"

NOTE: Add 7" to G +6" dimension for crank operation

FOW: Angle Guide Clearance Dimensions

Slat	Dimensions	Max Door Opening Widths		
		8'0"	15'0"	20'0"
C187	G	3"	3 1/2"	4"
C187	M	4 3/4"	6 1/4"	6 3/4"
C187	D	4 1/2"	4 1/2"	5"

Slat	Dimensions	Max Door Opening Widths				
		9'0"	15'0"	20'0"	30'0"	40'0"
C275, F265	G	3"	3 1/2"	4"	4 1/2"	5 5/8"
C275, F265	M	5 1/4"	5 3/4"	7 1/4"	9 1/4"	10 1/2"
C275, F265	D	4 1/2"	5"	5"	6"	6"

NOTE: Add 7" to G +6" dimension for crank operation

Dimension Charts: Model 610

Model 610 Between Jamb Mounted

BJ: Slat Data

Slat	Opening Width	Standard	Optional
C187	Thru 15'4"	22 ga.	20,18 ga. or 22,20 ga. ss
C275	Thru 18'4"	22 ga.	20 ga. or 22,20 ga. ss
C275	Thru 25'4"	20 ga.	16,18 ga. or 20 ga. ss
C275	Thru 30'4"	18 ga.	16 ga.
F265	Thru 18'4"		22, 20,18,16 ga. or 22,20 ga. ss
F265	Thru 25'4"		20, 18,16 ga. or 20 ga. ss
F265	Thru 30'4"		18, 16 ga.

BJ: Headroom Clearance Dimensions

Slat	Opening Height	A Dimension Max Door Opening Widths 15'4"
C187	Thru 6'0"	14"
C187	Thru 11'0"	14"
C187	Thru 18'0"	16"
C187	Thru 21'0"	18"
C187	Thru 30'0"	24"

NOTE: Consult factory for doors wider than 30'4"

Slat	Opening Height	A Dimension Max Door Opening Widths		
		20'0"	24'0"	30'0"
C275	Thru 6'0"	14"	14"	18"
C275	Thru 8'0"	16"	16"	18"
C275	Thru 9'0"	16"	18"	20"
C275	Thru 11'0"	16"	18"	20"
C275	Thru 13'0"	18"	18"	20"
C275	Thru 16'0"	18"	20"	22"
C275	Thru 18'0"	20"	22"	24"
C275	Thru 21'0"	22"	22"	24"
C275	Thru 23'0"	22"	24"	24"
C275	Thru 25'0"	24"	24"	26"
C275	Thru 28'0"	24"	24"	26"
C275	Thru 30'0"	26"	26"	28"

NOTE: Consult factory for doors wider than 30'4"

Dimension Charts: Model 610

BJ: Headroom Clearance Dimensions

Slat	Opening Height	A Dimension Max Door Opening Widths		
		20'0"	24'0"	30'0"
F265	Thru 6'0"	16"	16"	18"
F265	Thru 8'0"	18"	18"	20"
F265	Thru 9'0"	18"	18"	20"
F265	Thru 11'0"	18"	18"	20"
F265	Thru 13'0"	20"	20"	20"
F265	Thru 16'0"	20"	20"	22"
F265	Thru 18'0"	20"	22"	24"
F265	Thru 21'0"	22"	24"	24"
F265	Thru 23'0"	22"	24"	24"
F265	Thru 25'0"	24"	24"	26"
F265	Thru 28'0"	26"	26"	26"
F265	Thru 30'0"	26"	26"	28"

NOTE: Consult factory for doors wider than 30'4"

BJ: Guide Clearance Dimensions

Slat	Dimensions	Max Door Opening Widths		
		8'0"	15'0"	20'0"
C187	G	3"	3 1/2"	4"
C187	D	4 1/2"	4 1/2"	5"

Slat	Dimensions	Max Door Opening Widths				
		9'0"	15'0"	20'0"	30'0"	40'0"
C275, F265	G	3"	3 1/2"	4"	5 5/8"	5 5/8"
C275, F265	D	4 1/2"	5"	5"	6"	6"