



Dimension Charts for Advanced Rolling Steel Doors: RapidSlat® Models 611/621/626

Please be advised that the dimensions provided below are approximations based on standard offerings. If options are added or sideroom and headroom clearances are tight on your projects, please be sure to work with the factory for the most accurate data based on your jobs needs.

Models 611/621/626 Face of Wall Mounted

Slat Data

Model	Slat	Opening Width	Standard	Optional
611	C187*	Thru 15'4"	22 ga.	20,18 ga. or 22,20 ga. ss or .04" (18 ga.) Aluminum
611	C275	Thru 15'4"	22 ga.	20,18 ga. or 22,20 ga. ss or .05" (18 ga.) Aluminum
611	C275	Thru 18'4"	22 ga.	20,18 ga. or 22,20 ga. ss
611	C275	Thru 25'4"	20 ga.	18 ga. or 20 ga. ss
611	C275	Thru 30'0"	18 ga.	
611/621	F265	Thru 15'4"	22 ga.	20,18 ga. or 22,20 ga. ss or .05" (16 ga.) Aluminum
611/621	F265	Thru 18'4"	22 ga.	20,18 ga. or 22,20 ga. ss
611/621	F265	Thru 25'4"	20 ga.	18 ga. or 20 ga. ss
611/621	F265	Thru 30'0"	18 ga.	
611/621	FE265	Thru 25'4"	14 ga.	
626	F265i	Thru 30'4"	24/24 ga.	Front of slat: 22,20,18 ga. or 22,20 ga. ss or .04" (18 ga.) Aluminum Back of slat: 22 ga. steel; 24 ga. ss, .025" (22 ga.) Aluminum

*C-187 slat limited to 15'4" in width.

NOTE: 18 ga. C275 and F265 slat profiles on Model 610S are available with full fenestration or partial curtain fenestration

Slats are galvanized and painted steel, stainless steel (ss) or aluminum.

Slat	R-value	U-value	STC Rating
F265i	7.7	0.13	21

Dimension Charts: RapidSlat® Models 611/621/626

FOW: Headroom Clearance Dimensions

Slat	Opening Height	A Dimension
		Max Door Opening Widths 15'4"
C187	Thru 8'4"	14"
C187	Thru 13'4"	16"
C187	Thru 20'0"	18"

NOTE: Consult factory for doors wider than 30'0"

Slat	Opening Height	A Dimension		
		Max Door Opening Widths		
		18'4"	25'4"	30'0"
C275	Thru 5'4"	14"	14"	16"
C275	Thru 6'4"	16"	16"	16"
C275	Thru 7'4"	16"	18"	-
C275	Thru 11'4"	18"	18"	-
C275	Thru 12'4"	18"	20"	-
C275	Thru 16'4"	20"	-	-
C275	Thru 20'0"	20"	-	-

NOTE: Consult factory for doors wider than 30'0"

Slat	Opening Height	A Dimension		
		Max Door Opening Widths		
		18'4"	25'4"	30'0"
F265	Thru 5'4"	16"	16"	16"
F265	Thru 10'4"	18"	18"	-
F265	Thru 20'0"	20"	-	-

NOTE: Consult factory for doors wider than 30'0"

Slat	Opening Height	A Dimension	
		Max Door Opening Widths	
		18'4"	25'4"
FE265	Thru 5'4"	16"	16"
FE265	Thru 10'4"	18"	18"
FE265	Thru 15'4"	20"	20"
FE265	Thru 20'0"	20"	22"

NOTE: Consult factory for doors wider than 30'0"

Slat	Opening Height	A Dimension		
		Max Door Opening Widths		
		18'4"	25'4"	30'0"
F265i	Thru 5'4"	16"	16"	18"
F265i	Thru 9'4"	18"	20"	20"
F265i	Thru 13'4"	20"	22"	-
F265i	Thru 18'4"	22"	-	-
F265i	Thru 20'0"	24"	-	-

NOTE: Consult factory for doors wider than 30'0"