



Dimension Charts for Rolling Steel Doors: Model 620

Please be advised that the dimensions provided below are approximations based on standard offerings. If options are added or sideroom and headroom clearances are tight on your projects, please be sure to work with the factory for the most accurate data based on your jobs needs.

Model 620 Face-of-Wall Mounted

FOW: Slat Data

Slat	Opening Width	Standard	Optional
F265	Thru 18'4"	22 ga.	20,18,16 ga. or 22,20 ga. ss
F265	Thru 25'4"	20 ga.	18,16 ga. or 20 ga. ss
F265	Thru 30'4"	18 ga.	16 ga.

FOW: Headroom Clearance Dimensions

Slat	Opening Height	A Dimension Max Door Opening Widths		
		20'0"	24'0"	30'0"
F265	Thru 6'0"	16"	16"	18"
F265	Thru 8'0"	18"	18"	20"
F265	Thru 9'0"	18"	18"	20"
F265	Thru 11'0"	18"	18"	20"
F265	Thru 13'0"	20"	20"	20"
F265	Thru 16'0"	20"	20"	22"
F265	Thru 18'0"	20"	22"	24"
F265	Thru 21'0"	22"	24"	24"
F265	Thru 23'0"	22"	24"	24"
F265	Thru 25'0"	24"	24"	26"
F265	Thru 28'0"	26"	26"	26"
F265	Thru 30'0"	26"	26"	28"

NOTE: For Face of Wall Mount, Use *A+5" for electric
Consult factory for doors wider than 30'4"

FOW: Rolled Guide Clearance Dimensions

Dimensions	Max Door Opening Width 15'4"
G	2 1/2"
M	4 1/2"
D	5"

NOTE: For Face of Wall Mount, Add 7" to G +6" dimension for crank operation

FOW: Angle Guide Clearance Dimensions

Dimensions	Max Door Opening Widths 10'0"
G	3"
M	5 1/4"
D	4 1/2"

NOTE: For Face of Wall Mount, Add 7" to G +6" dimension for crank operation

Dimension Charts: Model 620

FOW: Angle Guides with Windbar Clearance Dimensions

Dimensions	Max Door Opening Widths				
	9'0"	15'0"	20'0"	30'0"	40'0"
G	3"	3 1/2"	4"	5 5/8"	5 5/8"
M	5 1/4"	6 1/4"	7 1/4"	10 1/4"	11 1/4"
D	4 1/2"	5 1/2"	5 1/2"	6"	6"

NOTE: For Face of Wall Mount, Add 7" to G +6" dimension for crank operation

Dimension Charts: Model 620

Model 620 Between Jamb Mounted

BJ: Slat Data

Slat	Opening Width	Standard	Optional
F265	Thru 18'4"	22 ga.	20,18,16 ga. or 20 ga. ss
F265	Thru 25'4"	20 ga.	18,16 ga. or 20 ga. ss
F265	Thru 30'4"	18 ga.	16 ga.

BJ: Headroom Clearance Dimensions

Slat	Opening Height	A Dimension Max Door Opening Widths		
		20'0"	24'0"	30'0"
F265	Thru 6'0"	16"	16"	18"
F265	Thru 8'0"	18"	18"	20"
F265	Thru 9'0"	18"	18"	20"
F265	Thru 11'0"	18"	18"	20"
F265	Thru 13'0"	20"	20"	20"
F265	Thru 16'0"	20"	20"	24"
F265	Thru 18'0"	20"	22"	24"
F265	Thru 21'0"	22"	24"	24"
F265	Thru 23'0"	22"	24"	24"
F265	Thru 25'0"	24"	24"	26"
F265	Thru 28'0"	26"	26"	26"
F265	Thru 30'0"	26"	26"	28"

NOTE: Consult factory for doors wider than 30'4"

BJ: Guide Clearance Dimensions

Dimensions	Max Door Opening Widths				
	9'0"	15'0"	20'0"	30'0"	40'0"
G	3"	3 1/2"	4"	5 5/8"	5 5/8"
D	4 1/2"	5"	5"	6"	6"

BJ: Angle Guides with Windbar Clearance Dimensions

Dimensions	Max Door Opening Widths				
	9'0"	15'0"	20'0"	30'0"	40'0"
G	3"	3 1/2"	4"	5 5/8"	5 5/8"
M	5 1/4"	6 1/4"	7 1/4"	10 1/4"	11 1/4"
D	4 1/2"	5 1/2"	5 1/2"	6"	6"