



Dimension Charts for Rolling Steel Doors: Model 625

Please be advised that the dimensions provided below are approximations based on standard offerings. If options are added or sideroom and headroom clearances are tight on your projects, please be sure to work with the factory for the most accurate data based on your jobs needs.

Model 625 Face-of-Wall Mounted

FOW: Slat Data

Slat	Opening Width	Standard	Optional
F265i	Thru 30'4"	24/24 ga.	Front of slat: 22,20,18 ga. or 22,20 ga. ss Back of slat: 24,22 ga. or 22 ga. ss
R-value	Smoke Generation	Flame Spread	STC Rating
7.7	10	5	21

FOW: Headroom Clearance Dimensions*

Slat	Opening Height	Max Door Opening Widths		
		20'0"	24'0"	30'0"
F265i	Thru 6'0"	16"	16"	18"
F265i	Thru 8'0"	18"	18"	20"
F265i	Thru 9'0"	18"	18"	20"
F265i	Thru 11'0"	20"	20"	22"
F265i	Thru 13'0"	20"	20"	22"
F265i	Thru 16'0"	22"	24"	24"
F265i	Thru 18'0"	24"	24"	26"
F265i	Thru 21'0"	24"	24"	26"
F265i	Thru 23'0"	26"	26"	26"

*For Face of Wall Mount; Use A+3" (without hood flange) for manually operated; A+5" (without hood flange) for motor operation

NOTE: Consult factory for doors wider than 23'0"

FOW: Angle Guide Clearance Dimensions*

Slat	Dimensions	Max Door Opening Width 13'0"
F265i	G	3"
F265i	M	5 1/4"
F265i	D	4 1/2"

NOTE: Max door opening width of 13'0" based on 24/24 standard offering on slats. Contact factory for more detailed information.

For Face of Wall Mount, Add 7" to G +6" dimension for crank operation.

FOW: Angle Guides with Windbar Clearance Dimensions

Slat	Dimensions	Max Door Opening Widths				
		9'0"	15'0"	20'0"	30'0"	40'0"
F265i	G	3"	3 1/2"	4"	5 5/8"	5 5/8"
F265i	M	5 1/4"	6 1/4"	7 1/4"	10 1/4"	11 1/4"
F265i	D	4 1/2"	5 1/2"	5 1/2"	6"	6"

NOTE: For Face of Wall Mount, Add 7" to G +6" dimension for crank operation

Dimension Charts: Model 625

Model 625 Between Jamb Mounted

BJ: Slat Data

Slat	Opening Width	Standard	Optional
F265i	Thru 30'4"	24/24 ga.	Front of slat: 22,20,18 ga. or 22,20 ga. ss Back of slat: 24,22 ga. or 22 ga. ss
R-value	Smoke Generation	Flame Spread	STC Rating
7.7	10	5	21

BJ: Headroom Clearance Dimensions

Slat	Opening Height	A Dimension Max Door Opening Widths		
		20'0"	24'0"	30'0"
F265i	Thru 6'0"	16"	16"	18"
F265i	Thru 8'0"	18"	18"	20"
F265i	Thru 9'0"	18"	18"	20"
F265i	Thru 11'0"	20"	20"	22"
F265i	Thru 13'0"	20"	20"	22"
F265i	Thru 16'0"	22"	24"	24"
F265i	Thru 18'0"	24"	24"	26"
F265i	Thru 21'0"	24"	24"	26"
F265i	Thru 23'0"	26"	26"	26"

NOTE: Consult factory for doors wider than 23'0"

BJ: Angle Guide Clearance Dimensions

Slat	Dimensions	Max Door Opening Widths				
		9'0"	15'0"	20'0"	30'0"	40'0"
F265i	G	3"	3 1/2"	4"	5 5/8"	5 5/8"
F265i	D	4 1/2"	5"	5"	6"	6"