



Dimension Charts for Rolling Steel Doors: Stormtite™ AP Model 627

Please be advised that the dimensions provided below are approximations based on standard offerings. If options are added or sideroom and headroom clearances are tight on your projects, please be sure to work with the factory for the most accurate data based on your jobs needs.

Stormtite™ AP Model 627 - Face-of-Wall Mounted

FOW: Slat Data

Slat	Opening Width	Standard	Optional
FIT	Thru 30'4"	24 ga.	22ga. SS, AL
R-value	Smoke Generation	Flame Spread	STC
10.9	55	0	Through curtain: 28 Installed system: 21

FOW: Headroom Clearance Dimensions

Opening Height	Dimension A Max Door Opening Widths		
	20'0"	24'0"	30'0"
Thru 6'0"	22"	22"	24"
Thru 8'0"	24"	24"	26"
Thru 9'0"	26"	26"	26"
Thru 11'0"	26"	26"	28"
Thru 13'0"	28"	28"	30"
Thru 16'0"	30"	30"	32"
Thru 18'0"	32"	32"	32"
Thru 19'0"	32"	34"	34"
> 19'0"	Consult Factory	Consult Factory	Consult Factory

FOW: Guide Clearance Dimensions no Windbar

Dimensions	Max Door Opening Width
	12'0"
G	3 1/2"
M	5 3/4"
D	5 11/16"

FOW: Guide Clearance Dimensions with Windbar

Dimensions	Max Door Opening Widths		
	15'0"	20'0"	30'0"
G	3 1/2"	4"	5 9/16"
M	6 1/4"	7 1/4"	9 1/4"
D	6 1/4"	6 3/16"	7 1/16"

Dimension Charts: Model 627

Stormtite™ AP Model 627 - Between Jamb Mounted

BJ: Slat Data

Slat	Opening Width	Standard	Optional
FIT	Thru 30'4"	24 ga.	22ga. SS, AL
R-value	Smoke Generation	Flame Spread	STC
10.9	55	0	Through curtain: 28 Installed system: 21

BJ: Headroom Clearance Dimensions

Opening Height	Dimension A Max Door Opening Widths		
	20'0"	24'0"	30'0"
Thru 6'0"	22"	24"	24"
Thru 8'0"	24"	24"	24"
Thru 9'0"	26"	26"	26"
Thru 11'0"	26"	26"	28"
Thru 13'0"	28"	28"	28"
Thru 16'0"	30"	30"	30"
Thru 18'0"	32"	32"	32"
Thru 19'0"	32"	34"	34"
> 19'0"	Consult Factory	Consult Factory	Consult Factory

BJ: Guide Clearance Dimensions no Windbar

Dimensions	Max Door Opening Width
	12'0"
G	3 1/4"
D	6 1/4"

BJ: Guide Clearance Dimensions with Windbar

Dimensions	Max Door Opening Widths		
	15'0"	20'0"	30'0"
G	3"	3 1/2"	5"
D	7 1/4"	7 1/4"	7 5/8"