



## Dimension Charts for Rolling Steel Doors: FireKing® Models 630/631/634/635

Please be advised that the dimensions provided below are approximations based on standard offerings. If options are added or sideroom and headroom clearances are tight on your projects, please be sure to work with the factory for the most accurate data based on your jobs needs.

### Model 630 Face-of Wall Mounted

#### FOW: Slat Data

Slat	Opening Width	Standard	Optional
C187	Thru 14'0"	22 ga.*	20,18 ga. or 22*,20 ga. ss
C187	Thru 20'0"	20 ga.	18 ga. or 20 ga. ss
C275	Thru 14'0"		22*, 20,18,16 ga. or 22*,20 ga. ss
C275	Thru 20'0"		20,18,16 ga. or 20 ga. ss
C275	Thru 24'0"		18,16 ga.
F265	Thru 14'0"		22*,20,18 ga. or 22*,20 ga. ss
F265	Thru 20'0"		20,18 ga. or 20 ga. ss
F265	Thru 24'0"		18 ga.

NOTES: Slats are galvanized and painted or stainless steel (ss).  
Wider doors may be available, contact factory for more information.

\* Maximum wall opening height for 22 ga. is 12'0".

#### FOW: Headroom Clearance Dimensions

Slat	Max	Through 14'0" Wide		Through 20'0" Wide		Through 24'0" Wide	
		Dim A	Dim B	Dim A	Dim B	Dim A	Dim B
C187	Thru 10'0"	17 1/2"	19 5/8"	21 1/2"	23 5/8"		
C187	Thru 21'0"	21 1/2"	23 5/8"	21 1/2"	23 5/8"		
C187	Thru 24'0"	23 1/2"	25 5/8"	25 1/2"	27 5/8"		
C275	Thru 10'0"	19 1/2"	21 5/8"	21 1/2"	23 5/8"	21 1/2"	23 5/8"
C275	Thru 11'0"	19 1/2"	21 5/8"	21 1/2"	23 5/8"	23 1/2"	25 5/8"
C275	Thru 14'0"	21 1/2"	23 5/8"	21 1/2"	23 5/8"	23 1/2"	25 5/8"
C275	Thru 16'0"	21 1/2"	23 5/8"	21 1/2"	23 5/8"	25 1/2"	27 5/8"
C275	Thru 18'0"	21 1/2"	23 5/8"	25 1/2"	27 5/8"	■	■
C275	Thru 19'0"	23 1/2"	25 5/8"	25 1/2"	27 5/8"	■	■
C275	Thru 21'0"	23 1/2"	25 5/8"	27 1/2"	29 5/8"	■	■
C275	Thru 24'0"	25 1/2"	27 5/8"	■	■	■	■
F265	Thru 10'0"	21 1/2"	23 5/8"	21 1/2"	23 5/8"	21 1/2"	23 5/8"
F265	Thru 14'0"	21 1/2"	23 5/8"	21 1/2"	23 5/8"	23 1/2"	25 5/8"
F265	Thru 16'0"	23 1/2"	25 5/8"	23 1/2"	25 5/8"	25 1/2"	27 5/8"
F265	Thru 18'0"	23 1/2"	25 5/8"	23 1/2"	25 5/8"	■	■
F265	Thru 19'0"	23 1/2"	25 5/8"	25 1/2"	27 5/8"	■	■
F265	Thru 21'0"	23 1/2"	25 5/8"	27 1/2"	29 5/8"	■	■
F265	Thru 24'0"	■	■	■	■	■	■

NOTES: Height limit for non-masonry jambs is 12'0"

Add 2" for electric operation to B dimension

■ Consult Factory

## Dimension Charts: Models 630/631/634/635

Model 630 Angle Guide Dimensions

Slat	Jamb type	Max Wall Opening Widths	G	Setback	M
C187, C275, F265	<ul style="list-style-type: none"> <li>• Steel tube</li> <li>• Steel stud</li> <li>• Wood &amp; steel studs</li> <li>• Wood stud</li> </ul>	Thru 8'0"	3 3/4"	13/16"	
		Thru 12'0"	4 1/4"	13/16"	
		Thru 14'0"	4 3/4"	1"	
	<ul style="list-style-type: none"> <li>• Filled concrete masonry unit or hard-fired brick</li> <li>• Unfilled concrete masonry unit or soft brick</li> <li>• Steel jamb</li> <li>• Concrete jamb</li> </ul>	Thru 8'0"	3 1/4"		5 1/2"
		Thru 12'0"	3 3/4"		6"
		Thru 14'0"	4"		5 3/4"
		Thru 16'0"	4 1/4"		6"
		Thru 20'0"	4 3/4"		7"
		Thru 24'0"	5 3/4"		8"

For max wall opening height of 12 ft.

**Dimension Charts: Models 630/631/634/635**

**Model 631 Face-of Wall Mounted**

**FOW: Slat Data**

<b>Slat</b>	<b>Opening Width</b>	<b>Standard</b>	<b>Optional</b>
C187	Thru 14'0"	24 ga.	22 ga.
F265	Thru 14'0"	24 ga.	22 ga.

Slats are galvanized and painted.

## Dimension Charts: Models 630/631/634/635

### Model 634 Face-of Wall Mounted

#### Slat Data

Slat	Opening Width	Standard	Optional
C187	Thru 20'0"	20 ga.	18 ga. or 20,18 ga. ss
C275	Thru 20'0"	20 ga.	18 ga. or 20,18 ga. ss
	Thru 41'2"	18 ga.	16 ga.
F265	Thru 20'0"	20 ga.	18 ga. or 20,18 ga. ss
	Thru 41'2"	18 ga.	

Slats are galvanized and painted or stainless steel (ss).

#### Slat Data

Slat	Opening Width	Standard	Optional
F265 with back cover	Thru 24'0"	24 ga. front 24 ga. back	22 ga. front 22 ga. back

Slats are galvanized and painted.

### Model 635 Face-of Wall Mounted/Between Jamb Mount

#### Slat Data

Slat	Opening Width	Standard	Optional
F265 with back cover	Thru 24'0"	24 ga. front 24 ga. back	22 ga. front 22 ga. back

Slats are galvanized and painted.