



Dimension Charts for Security Grilles: Models 670/671

Please be advised that the dimensions provided below are approximations based on standard offerings. If options are added or sideroom and headroom clearances are tight on your projects, please be sure to work with the factory for the most accurate data based on your jobs needs.

Models 670-671 Security Grilles Face of Wall Mounted

Headroom and Sideroom Clearance Dimensions

Opening Height	Dimension A	Dimension B	Dimension C		Add to "A"
	A	B	Operation	C	
Thru 6'7"	15"	16"	Chain STD	9 1/4"	
Thru 10'10"	17"	18"	F.O.H. Chain	5 1/2"	+10" (254 mm)
Thru 15'10"	19"	20"	Awning Crank	5 1/2"	+12" (305 mm)
Thru 19'6"	21"	22"	Push-Up	5 1/2"	
Thru 22'6"	23"	24"	Electric Model RMX®	9 1/4"	
Thru 24'0"	25"	26"	Electric Model RSX®	9 1/4"	
			Electric Model RHX®	6 3/4"	S70
				5 1/2"	Special Mart

*If Motor Operated add 2 1/4" (57 mm) to B

*If Safety Edge add 3 3/4" (95 mm) to B

Grille Upsets

Manual		Electric		Extr. T Tubular DABB
Without weather strip	With weather strip	Without safety edge	With safety edge	
1 3/4"	2 3/4"	3 3/4"	5 1/4"	
2 1/2"	3 3/4"	4 3/4"	6 1/4"	
1 3/4"	2 3/4"	3 3/4"	5 1/4"	

Models 670-671 Security Grilles Between Jambs Mounted

Headroom and Sideroom Clearance Dimensions

Opening Height	Dimension A	Dimension B	Dimension C		Add to "A"
	A	B	Operation	C	
Thru 6'7"	15"	16"	Chain STD	9 1/4"	+10" (254 mm) +12" (305 mm)
Thru 10'10"	17"	18"	F.O.H. Chain	5 1/2"	
Thru 15'10"	19"	20"	Awning Crank	5 1/2"	
Thru 19'6"	21"	22"	Push-Up	5 1/2"	
Thru 22'6"	23"	24"	Electric Model RMX®	9 1/4"	
Thru 24'0"	25"	26"	Electric Model RSX®	9 1/4"	
			Electric Model RHX®	5 1/2"	

*If Motor Operated add 2 1/4" (57 mm) to B

*If Safety Edge add 3 3/4" (95 mm) to B

Grille Upsets

Manual		Electric		
Without weather strip	With weather strip	Without safety edge	With safety edge	
1 3/4"	2 3/4"	3 3/4"	5 1/4"	Extr. T
2 1/2"	3 3/4"	4 3/4"	6 1/4"	Tubular
1 3/4"	2 3/4"	3 3/4"	5 1/4"	DABB