



## Dimension Charts for EverServe™ Models 610S/620S/625S

Please be advised that the dimensions provided below are approximations based on standard offerings. If options are added or sideroom and headroom clearances are tight on your projects, please be sure to work with the factory for the most accurate data based on your jobs needs.

### Models 610S/620S/625S Face of Wall Mounted

Slat Data				
Model	Slat	Opening Width	Standard	Optional
610S	C187*	Up to 15'4"	22 ga.	20,18 ga. or 22,20 ga. ss or .04" (18 ga.) Aluminum
610S	C275	Up to 20'0"	22 ga.	20,18 ga. or 22,20 ga. ss or .05" (16 ga.) Aluminum
610S	F265	Up to 20'0"	22 ga.	20,18 ga. or 22,20 ga. ss or .05" (16 ga.) Aluminum
620S	F265	Up to 20'0"	22 ga.	20,18 ga. or 22,20 ga. ss or .05" (16 ga.) Aluminum Front of slat: 22,20,18 ga. or 22,20 ga. ss or .04" (18 ga.) Aluminum
625S	F265i	Up to 20'0"	24/24 ga.	Back of slat: 22 ga. or 22 ga. ss; .025" (22 ga.) Aluminum

\*C-187 slat limited to 15'4" in width.  
 NOTE: 18 ga. C275 and F265 slat profiles on Model 610S are available with full fenestration or partial curtain fenestration  
 Slat are galvanized and painted steel, stainless steel (ss) or aluminum.

Slat	R-value	U-value	STC Rating
F265i	7.7	0.13	21

### Headroom Clearance Dimensions

Slat	Opening Height	Dimension A	Max Door Opening Width
C187	Thru 8'0"	14"	15'4"
C187	Thru 14'0"	16"	15'4"
C187	Thru 20'0"	18"	15'4"
C275	Thru 5'0"	14"	20'0"
C275	Thru 10'0"	16"	20'0"
C275	Thru 15'0"	18"	20'0"
C275	Thru 20'0"	20"	15'0"
F265	Thru 9'0"	16"	20'0"
F265	Thru 14'0"	18"	20'0"
F265	Thru 20'0"	20"	15'0"
F265i	Thru 7'0"	16"	20'0"
F265i	Thru 11'0"	18"	20'0"
F265i	Thru 16'0"	20"	11'0"
F265i	Thru 20'0"	22"	9'0"