

HIGH SPEED DOOR SYSTEMS



PRODUCT LINE

RAPIDFLEX® FABRIC DOORS
RAPIDFLEX® RUBBER DOORS
RAPIDFREEZE® FABRIC DOORS
RAPIDSHIELD® METAL DOORS
RAPIDVIEW® FULL-VIEW METAL DOORS

MODELS

990/991/992/993/994

995/995LH

997

998

999



INDUSTRY EXPERTS,
DELIVERING TOTAL SOLUTIONS



High Performance Doors That Are as Fast, Reliable and Versatile as your Business

The RapidFlex®, RapidFreeze®, RapidShield® and RapidView® series of high performance doors are engineered to allow maximum productivity with fast-acting curtains, high-cycle performance and resistance to damage from accidental collisions. With robust safety features and a pressure resistant design, these high speed doors will keep your facility running securely, efficiently and environmentally controlled.

General Features and Benefits

Springless, High Cycle Design

- Minimizes down-time, ideal for high cycle applications

Fast-acting

- Fully opens in 4 seconds or less*

Breakaway Bottom

- Designed to break away from the side guides
- Simple reset and self repair after a break-away event
- Impact detection

Airtight Guides (Model 991)

- Tight sealing guides resist air pressure
- Help control environments; minimize debris

Direct Gear Drive System

- Eliminates the wear and tear associated with conventional chain and sprocket systems
- Advanced gearbox design features door stop safety device

Robust Safety Features

- Dual infrared sensors
- Wireless bottom reversing edge
- Flexible bottom edge (Model 990)
- Built-in door stop device
- Safety light curtain minimizes contact with objects in the doorway
 - Integrated (Standard for Models 998 & 999)
 - Externally mounted (optional for Models 990-995)

Independently Tested

- Air infiltration (Model 991)
- Wind load

Hood Standard (Models 990, 991, 992, 993, 994, 995)

Padlockable Disconnect at Controller

Plug and Play Wiring


*Depending on opening height and door models

Cover image: Model 994, Blue

Image above: Model 995, Black




Standard Product Features



Patented Curtain Lock

Enables doors to be repaired quickly and in the field, unlike zippered doors. (Models 990 and 991).



Patented Roller Wind Strut

Heavy-duty strut with roller wind lock enhances curtain strength. (Models 993 and 994).



Wireless Reversing Edge

Designed to reverse with minimum contact load.



Obstruction Detection

Features two in-plane infrared sensors, minimizing contact with objects in the doorway. (Standard on Models 990-997. Optional on Models 998-999).




Traveling Wind Bar

Provides added structural support and enhanced operation in demanding operations (Model 995).



New Advanced Control Panel*

Features circular LED light ring with flexible activation profiles, automatic adjustment of operator frequency to prevent a fault or stopping the door.



Light Curtain Obstruction Detection

6' integrated light curtain (Models 998, 999). Front or rear mounted light curtain available in 3' or 6' (Models 990 through 995).



Direct Drive Motor

Advanced gearbox features door stop safety device is design to reduce maintenance costs and increase durability.



Patented Helical Design Head Plate

Prevents metal curtain contact and provides smooth operation. (Models 998 and 999).



Flexible Bottom Bar with Detachable Bottom Seal

Allows for easy replacement and troubleshooting. (Model 990).

* Subject to model selection. Late availability.

Options

Signaling Device Options

Red/green LED traffic light, horn/strobe combination, rotating warning light.

Actuation Options

Push button, key switch, pull switch, loop detector, motion detector, treadle switch, radio control. Wireless options: pull switch, 1 or 3-button push button, palm button.

Programmable LED Lighting System

3" tall light bar with red, yellow, green lights. Available in 1, 2, 3 or 4 strip options

Cooler Application

Air curtain options available included heated or non-heated, steel or stainless steel and various voltage offerings (Model 991).

Sensor Options

Designed to provide varying levels of functionality and performance.



BEA Widescan



BEA Falcon



BEA IS40/XL



Miller Edge M Wave




Optex OAM Explorer

HIGH SPEED FABRIC DOORS

Flexible Bottom
Fabric Door
RAPIDFLEX® 990












Fabric Door
RAPIDFLEX® 991



Strutted
Fabric Door
RAPIDFLEX® 992



Features

Application	Manufacturing; Distribution; Food/Beverage; Pharmaceutical	Manufacturing; Distribution; Food/Beverage; Cooler; Cold Storage; Pharmaceutical	Manufacturing; Distribution; Food/Beverage; Cold Storage						
Location of Opening (Mount)	Interior	Interior	Interior/Exterior (Mount Inside/Outside)						
Maximum Width*	12'	14'	16'						
Maximum Height*	12'	14'	15'						
Opening Speed	Up to 70"/sec	Up to 70"/sec	Up to 65"/sec						
Closing Speed	Up to 40"/sec	Up to 40"/sec	Up to 40"/sec						
Certified Air Tightness¹	N/A	< 0.236 cfm/sq ft	N/A						
Curtain Lock	Yes	Yes	N/A						
Break Away Self Reset	Yes	Yes	Yes						
Wind Load²	Up to 3.0 psf	Up to 7.5 psf	Up to 4.0 psf						
Wind Strut	N/A	N/A	1" strut standard						
Traveling Wind Bar	N/A	N/A	N/A						
Curtain Material	2 layers of light PVC-coated polyester with 1 layer of polyester weave	2 layers of PVC-coated polyester with 1 layer of polyester weave	Interior: 2 layers of PVC-coated polyester with 1 layer of polyester weave; Exterior/Interior: 3 layers of PVC-coated polyester with 2 layers of polyester weave						
Vision	Optional 20" high vision panels spaced evenly across width of door	Optional 20" high vision panels spaced evenly across width of door	Optional 20" high vision panels spaced evenly across width of door						
Operation	Direct drive motor and gearbox system with field changeable universal handing and door stop safety device	Direct drive motor and gearbox system with field changeable universal handing and door stop safety device	Direct drive motor and gearbox system with field changeable universal handing and door stop safety device						
Control Panel	Variable frequency drive NEMA 4X cULus listed; Onboard self diagnostic and service reminder Built-in padlockable fused disconnect	Variable frequency drive NEMA 4X cULus listed; Onboard self diagnostic and service reminder Built-in padlockable fused disconnect	Variable frequency drive NEMA 4X cULus listed; Onboard self diagnostic and service reminder Built-in padlockable fused disconnect						
Obstruction Safety Detection	Infrared sensors mounted in-plane to the door curtain at 18" and 50" - 54" from floor; Optional front or rear mounted light curtain.	Infrared sensors mounted in-plane to the door curtain at 18" and 50" - 54" from floor; Optional front or rear mounted light curtain.	Infrared sensors mounted in-plane to the door curtain at 18" and 50" - 54" from floor; Optional front or rear mounted light curtain.						
Reversing Safety Edge	Wireless reversing edge; Flexible bottom bar with detachable bottom seal	Wireless reversing edge	Wireless reversing edge						
Available Supply Voltages³	120V AC 1PH, 208V AC 1PH¹, 220V AC 1PH, 208V AC 3PH¹, 230V AC 3PH, 460V AC 3PH, 575V 3PH¹ (¹requires stand-alone mounted transformer)	120V AC 1PH, 208V AC 1PH¹, 220V AC 1PH, 208V AC 3PH¹, 230V AC 3PH, 460V AC 3PH, 575V 3PH¹ (¹requires stand-alone mounted transformer)	120V AC 1PH, 208V AC 1PH¹, 220V AC 1PH, 208V AC 3PH¹, 230V AC 3PH, 460V AC 3PH, 575V 3PH¹ (¹requires stand-alone mounted transformer)						
Hinged Guides	Provides easy access for maintenance	Provides easy access for maintenance	Provides easy access for maintenance						
Warranty	5-year limited on drive motor and gearbox; 1-year limited on all other components	5-year limited	5-year limited						
Curtain Color Options									
Actual colors may vary due to fluctuation in the printing process. Always request a color sample from your Overhead Door™ Distributor for accurate color matching.									
	Red	Blue	White	Gray	Black (991/992 only)	Orange (991/992 only)	Yellow (991/992 only)	FDA Royal Blue (991/992 only)	FDA White (991/992 only)

Notes

² Wind load is the ultimate pressure tested
at door width of 12'.

¹ Air tightness is independently tested to
ASTM E283 test standard.
Wind load is the ultimate pressure tested
at door width of 10'.

² Wind load is the ultimate pressure tested
at door width of 16'.

* Height and width of door may affect opening speed. Please consult factory for specifics.



Strutted Heavy-Duty
Fabric Door

RAPIDFLEX® 993



Manufacturing; Distribution;
Auto/Transit; Parking; Food/Beverage

Exterior (Mount Inside/Outside)

20'

20'

Up to 65"/sec

Up to 40"/sec

N/A

N/A

Yes

Up to 19.5 psf

Metal struts with roller wind lock

N/A

3 layers of PVC-coated polyester with
2 layers of polyester weave

Optional 20" vision panels spaced
evenly across width of door

Direct drive motor and gearbox system
with field changeable universal handing
and door stop safety device

Variable frequency drive
NEMA 4X cULus listed;
Onboard self diagnostic and service reminder;
Built-in padlockable fused disconnect


Infrared sensors mounted in-plane to the door
curtain at 18" and 50" - 54" from floor; Optional front
or rear mounted light curtain.

Wireless reversing edge


120V AC 1PH, 208V AC 1PH[†], 220V AC 1PH,
208V AC 3PH[†], 230V AC 3PH, 460V AC 3PH, 575V 3PH[†]
([†]requires stand-alone mounted transformer)

Provides easy access for maintenance


5-Year Limited




Red



Blue



Orange



Gray

Above colors also available for Model 992 with
optional exterior/interior curtain material.

**RAPIDFLEX®/RAPIDFREEZE®
FABRIC DOORS**

MODELS 990/991/992/993

Ideal for separating controlled environment spaces such as food and
beverage facilities, high traffic zones, storage rooms, freezer and cooler
applications and manufacturing areas to prevent cross-contamination.

- Dual wind lock allows for quiet and smooth operation
on Models 990 and 991
- Flexible bottom bar with detachable seal for easy replacement and
troubleshooting on Model 990
- Heavy-duty strut with roller wind lock on Model 993
- Air curtain options available for Model 991



Model 994, Gray, windows

² Wind load is the ultimate pressure tested at door
width of 20'.

HIGH SPEED FABRIC, RUBBER & METAL DOORS

Strutted Maximum Strength
Fabric Door
RAPIDFLEX® 994



Extreme
Rubber Door
RAPIDFLEX® 995



Low Headroom
Rubber Door
RAPIDFLEX® 995LH



Extreme
Fabric Door
RAPIDFREEZE® 997



Features

Application	Manufacturing; Distribution; Mining; Auto/Transit; Parking	Manufacturing; Distribution; Mining; Auto/Transit; Parking	Manufacturing; Distribution; Mining; Auto/Transit; Parking	Cold storage; Food/Beverage; Distribution
Location of Opening (Mount)	Exterior (Mount Inside/Outside)	Exterior (Mount Inside/Outside)	Exterior (Mount Inside/Outside)	Interior
Maximum Width*	24'	30'	22'	12'
Maximum Height*	18' at 24' wide or 20' at 23' wide	30'	10'	18'
Opening Speed	Up to 55"/sec	Up to 50"/sec	Up to 30"/sec	Up to 80"/sec
Closing Speed	Up to 40"/sec	Up to 40"/sec	Up to 20"/sec	Up to 40"/sec
Certified Air Tightness ¹	N/A	N/A	N/A	N/A
Curtain Lock	N/A	Yes	Yes	N/A
Break Away Self Reset	Yes	Yes	No ¹	Yes
Wind Load ²	Up to 22.0 psf	Up to 27.0 psf	Up to 27.0 psf	Up to 2.0 psf
Wind Strut	4" articulating roller wind strut	N/A	N/A	N/A
Traveling Wind Bar	N/A	Optional	N/A	N/A
Curtain Material	3 layers of PVC-coated polyester with 2 layers of polyester weave	5 layers of NBR Rubber with 4 layers of polyester weave	5 layers of NBR Rubber with 4 layers of polyester weave	2 layers of PVC-coated polyester with 1 layer of polyester weave and conductive plus radiant insulation
Vision	Optional 20" high vision panels spaced evenly across width of door	Optional 20" high vision panels spaced evenly across width of door	Optional 20" high vision panels spaced evenly across width of door	N/A
Operation	Direct drive motor and gearbox system with field changeable universal handing and door stop safety device	Direct drive motor and gearbox system with field changeable universal handing and door stop safety device	Direct drive motor and gearbox system with field changeable universal handing and door stop safety device	Direct drive motor and gearbox system with field changeable universal handing and door stop safety device
Control Panel	Variable frequency drive NEMA 4X cULus listed; Onboard self diagnostic and service reminder; Built-in padlockable fused disconnect	Variable frequency drive NEMA 4X cULus listed; Onboard self diagnostic and service reminder; Built-in padlockable fused disconnect	Variable frequency drive NEMA 4X cULus listed; Onboard self diagnostic and service reminder; Built-in padlockable fused disconnect	Variable frequency drive NEMA 4X cULus listed; Onboard self diagnostic and service reminder; Built-in padlockable fused disconnect; Includes power for guide heater and air curtain
Obstruction Safety Detection	Infrared sensors mounted in-plane to the door curtain at 18" and 50"- 54" from floor; Optional front or rear mounted light curtain.	Infrared sensors mounted in-plane to the door curtain at 4.5" and 50"- 54" from floor; Optional front or rear mounted light curtain.	Infrared sensors mounted in-plane to the door curtain at 4.5" and 50"- 54" from floor; Optional front or rear mounted light curtain.	Infrared sensors mounted in-plane to the door curtain at 16" and 50"- 54" from floor
Reversing Safety Edge	Wireless reversing edge	Wireless reversing edge	Wireless reversing edge	Wireless reversing edge
Available Supply Voltages ³	208V AC 3PH ¹ , 230V AC 3PH, 460V AC 3PH, 575V AC 3PH ¹ (*requires stand-alone mounted transformer)	208V AC 3PH ¹ , 230V AC 3PH, 460V AC 3PH, 575V AC 3PH ¹ (*requires stand-alone mounted transformer)	208V AC 3PH ¹ , 230V AC 3PH, 460V AC 3PH, 575V AC 3PH ¹ (*requires stand-alone mounted transformer)	230V AC 3PH, 460V AC 3PH, 575V AC 3PH ¹ (*requires stand-alone mounted transformer)
Hinged Guides	Provides easy access for maintenance	N/A	N/A	N/A
Warranty	5-Year Limited	5-Year Limited	5-Year Limited	5-Year Limited
Curtain Color Options	<p>Actual colors may vary due to fluctuation in the printing process. Always request a color sample from your Overhead Door™ Distributor for accurate color matching.</p> <div> <div>Red</div> <div>Blue</div> <div>Orange</div> <div>Gray</div> <div>Black</div> <div>Blue</div> <div>Black</div> <div>Blue</div> <div>Red</div> <div>Blue</div> <div>White</div> <div>Gray</div> </div>			
Notes	² Wind load is the ultimate pressure tested at door width of 20'. ² Wind load is the ultimate pressure tested at door width of 19'. ¹ Automatic reset not available with low headroom model. Updated guide design allows for easy manual reset. ² Wind load is the ultimate pressure tested at door width of 19'. ² Wind load is the ultimate pressure tested at door width of 10'. ³ Applications with air curtain may require 460V or 575V.			

* Height and width of door may affect opening speed. Please consult factory for specifics.



Metal Door
RAPIDSHIELD® 998



Parking garages, Manufacturing,
Auto Dealerships

**Full-View
Metal Door**
RAPIDVIEW® 999



Auto Dealerships, Retail,
Manufacturing

**Interior/Exterior
(Mount Inside)**

**Interior/Exterior
(Mount Inside)**

26'

20'

21'

21'

Up to 80"/sec

Up to 80"/sec

Up to 20"/sec

Up to 20"/sec

N/A

N/A

N/A

N/A

N/A

N/A

Up to 100.0 psf*

Up to 50.0 psf

N/A

N/A

N/A

N/A

Dual-walled aluminum

Aluminum and scratch-resistant
polycarbonate

Optional scratch-resistant
polycarbonate panels

Scratch-resistant
polycarbonate panel

Direct drive motor and gearbox system
with field changeable universal handing
and door stop safety device

Direct drive motor and gearbox system
with field changeable universal handing
and door stop safety device

Variable frequency drive NEMA 4X cULus listed;
Onboard self diagnostic and service reminder;
Built-in padlockable fused disconnect

Variable frequency drive NEMA 4X cULus listed;
Onboard self diagnostic and service reminder;
Built-in padlockable fused disconnect

Integrated light curtain

Integrated light curtain

Wireless reversing edge

Wireless reversing edge

230V AC 3PH, 460V AC 3PH,
575V AC 3PH¹
(*requires stand-alone mounted transformer)

230V AC 3PH, 460V AC 3PH,
575V AC 3PH¹
(*requires stand-alone mounted transformer)

Provides easy access for maintenance


Provides easy access for maintenance

5-Year Limited

5-Year Limited



Silver powder coat made
to mimic anodized aluminum



Approximately 200 RAL powder coat finishes available.

RAPIDFLEX® FABRIC & RUBBER DOORS

MODELS 994/995/995LH/997

Well-suited for applications where forklifts and commercial vehicles can quickly enter from the outside while resisting strong wind and the elements. Ideal for manufacturing facilities or extreme environments.

- Staged head plate design for easy installation
- Heavy-duty strut with roller wind lock on Model 994
- Actively heated Thermoguides™ on Model 997 ensures the complete height of the guide has uniform temperature to prevent condensation
- Powder coated high visibility guides (Standard)
- Model 995LH is specifically designed for applications with low headroom



Model 995LH

RAPIDSHIELD®/ RAPIDVIEW® METAL DOORS

MODELS 998/999

Deliver security and durability with opening speed of up to 80" per second.

- Model 998 provides a solid aluminum curtain. Ideal for applications where security and privacy are a priority.
- Model 999 is a full-view door with polycarbonate panels for light infiltration and is perfect for high traffic applications requiring aesthetic appeal and visibility.
- Model 998 available with FBC approved HVHZ impact resistance.
- Optional perforated, vision or insulated slats available.

² Wind load is the ultimate pressure tested at door width of 15'.

* Up to 50.0 psf with optional vision panels.

² Wind load is the ultimate pressure tested at door width of 15'.



Model 999

Tools to help you
get the job done.



Architect's Edge

24/7 Self-service options at overheaddoor.com

- Custom Automated Drawing Generator
- Specs
- CAD Drawings
- BIM Object Library
- Continuing Education
- Architectural Services Contact

The original, innovative choice for unequalled quality and service.

Overhead Door Corporation pioneered the sectional garage door industry, inventing the first sectional garage door in 1921 and the first electric door operator in 1926. Today, we continue to be the industry leader through the strength of our product innovation, superior craftsmanship and outstanding customer support, underscoring a legacy of quality, expertise and integrity. That's why design and construction professionals specify Overhead Door™ products more often than any other brand. Our family of over 400 Overhead Door™ Distributors across the U.S. and Canada not only share our name and logo, but also our commitment to excellence.



**INDUSTRY EXPERTS,
DELIVERING TOTAL SOLUTIONS**



2501 S. State Hwy. 121 Bus., Suite 200, Lewisville, TX 75067
1-800-929-DOOR • sales@overheaddoor.com
overheaddoor.com