

HIGHSPEED DOOR COMPARISON CHART

FLEXIBLE BOTTOM
FABRIC DOOR
RAPIDFLEX®
MODEL 990

FABRIC DOOR
RAPIDFLEX®
MODEL 991

STRUTTED
FABRIC DOOR
RAPIDFLEX®
MODEL 992

STRUTTED HEAVY-DUTY
FABRIC DOOR
RAPIDFLEX®
MODEL 993

STRUTTED MAXIMUM
STRENGTH FABRIC DOOR
RAPIDFLEX®
MODEL 994

EXTREME
RUBBER DOOR
RAPIDFLEX®
MODEL 995

FREEZER AND COOLER
FABRIC DOOR
RAPIDFREEZE®
MODEL 997

METAL DOOR
RAPIDSHIELD®
MODEL 998

FULL-VIEW
METAL DOOR
RAPIDVIEW®
MODEL 999

High performance doors that are as fast, reliable and versatile as your business.




















FEATURES	GENERAL SPECIFICATIONS								
Application	Manufacturing; Distribution; Food/Beverage; Pharmaceutical	Manufacturing; Distribution; Food/Beverage; Cold Storage, Cooler; Pharmaceutical	Manufacturing; Distribution; Food/Beverage; Cold Storage	Manufacturing; Distribution; Auto/Transit; Parking; Food/Beverage	Manufacturing; Distribution; Mining; Auto/Transit; Parking	Manufacturing; Distribution; Mining; Auto/Transit; Parking	Cold storage; Food/Beverage; Distribution	Parking garages, Manufacturing, Auto dealerships	Auto dealerships, Retail, Manufacturing
Location of opening (mount)	Interior	Interior	Interior/Exterior (mount inside/outside)	Exterior (mount inside/outside)	Exterior (mount inside/outside)	Exterior (mount inside/outside)	Interior	Interior/Exterior (mount inside)	Interior/Exterior (mount inside)
Maximum width	12'	14'	16′	20'	24'	30′	12'	26'	20'
Maximum height	12'	14'	15′	20′	18' at 24' wide or 20' at 23' wide	30′	18′	21′	21′
Maximum opening speed	Up to 70"/sec	Up to 70"/sec	Up to 65"/sec	Up to 65"/sec	Up to 55"/sec	Up to 50"/sec	Up to 80"/sec	Up to 80"/sec	Up to 80"/sec
Maximum closing speed	Up to 40"/sec	Up to 40"/sec	Up to 40"/sec	Up to 40"/sec	Up to 40"/sec	Up to 40"/sec	Up to 40"/sec	Up to 20"/sec	Up to 20"/sec
Certified air tightness ¹	N/A	< 0.236 cfm/sq ft	N/A	N/A	N/A	N/A	N/A	N/A	N/A
Curtain lock	Yes	Yes	N/A	N/A	N/A	Yes	N/A	N/A	N/A
Breakaway self reset	Yes	Yes	Yes	Yes	Yes	Yes	Yes	N/A	N/A
Wind load ²	Up to 3.0 psf	Up to 7.5 psf	Up to 4.0 psf	Up to 19.5 psf	Up to 22.0 psf	Up to 27.0 psf	Up to 2.0 psf	Up to 100.0* psf	Up to 50.0 psf
Wind strut	N/A	N/A	1" strut standard	Metal struts with roller windlocks	4" articulating roller wind strut	N/A	N/A	N/A	N/A
Curtain material	2 layers of light PVC-coated polyester with 1 layer of polyester weave	2 layers of PVC-coated polyester with 1 layer of polyester weave	Interior: 2 layers of PVC-coated polyester with 1 layer of polyester weave Exterior/Interior: 3 layers of PVC-coated polyester with 2 layers of polyester weave	3 layers of PVC-coated polyester with 2 layers of polyester weave	3 layers of PVC-coated polyester with 2 layers of polyester weave	5 layers of NBR Rubber with 4 layers of polyester weave	2 layers of PVC-coated polyester with 1 layer of polyester weave and conductive plus radiant insulation	Dual-walled aluminum	Aluminum and scratch-resistant polycarbonate
Vision	Optional 20" high vision panels spaced evenly across width of door	Optional 20" high vision panels spaced evenly across width of door	Optional 20" high vision panels spaced evenly across width of door	Optional 20" high vision panels spaced evenly across width of door	Optional 20" high vision panels spaced evenly across width of door	Optional 10" x 20" vision panels (maximum quantity depending on door size)	N/A	Optional scratch-resistant polycarbonate panels	Scratch-resistant polycarbonate panels
Operation	Direct drive motor and gearbox system with field changeable universal handing and door stop safety device	Direct drive motor and gearbox system with field changeable universal handing and door stop safety device	Direct drive motor and gearbox system with field changeable universal handing and door stop safety device	Direct drive motor and gearbox system with field changeable universal handing and door stop safety device	Direct drive motor and gearbox system with field changeable universal handing and door stop safety device	Direct drive motor and gearbox system with field changeable universal handing and door stop safety device	Direct drive motor and gearbox system with field changeable universal handing and door stop safety device	Direct drive motor and gearbox system with field changeable universal handing and door stop safety device	Direct drive motor and gearbox system with field changeable universal handing and door stop safety device
Control panel	Variable frequency drive NEMA 4X cULus listed; Onboard self diagnostic and service reminder; Built-in padlockable fused disconnect	Variable frequency drive NEMA 4X cULus listed; Onboard self diagnostic and service reminder; Built-in padlockable fused disconnect	Variable frequency drive NEMA 4X cULus listed; Onboard self diagnostic and service reminder; Built-in padlockable fused disconnect	Variable frequency drive NEMA 4X cULus listed; Onboard self diagnostic and service reminder; Built-in padlockable fused disconnect	Variable frequency drive NEMA 4X cULus listed; Onboard self diagnostic and service reminder; Built-in padlockable fused disconnect	Variable frequency drive NEMA 4X cULus listed; Onboard self diagnostic and service reminder; Built-in padlockable fused disconnect	Variable frequency drive NEMA 4X cULus listed; Onboard self diagnostic and service reminder; Built-in padlockable fused disconnect; Includes power for guide heater and air curtain	Variable frequency drive NEMA 4X cULus listed; Onboard self diagnostic and service reminder; Built-in padlockable fused disconnect	Variable frequency drive NEMA 4X cULus listed; Onboard self diagnostic and service remind Built-in padlockable fused disconnect
Obstruction safety detection	Infrared sensors mounted in-plane to the door curtain at 18" and 50"- 54" from floor; Optional front or rear mounted light curtain	Infrared sensors mounted in-plane to the door curtain at 18" and 50"- 54" from floor; Optional front or rear mounted light curtain	Infrared sensors mounted in-plane to the door curtain at 18" and 50"- 54" from floor; Optional front or rear mounted light curtain	Infrared sensors mounted in-plane to the door curtain at 18" and 50"- 54" from floor; Optional front or rear mounted light curtain	Infrared sensors mounted in-plane to the door curtain at 18" and 50" 54" from floor; Optional front or rear mounted light curtain	Infrared sensors mounted in-plane to the door curtain at 4.5" and 50"54" from floor; Optional front or rear mounted light curtain	Infrared sensors mounted in-plane to the door curtain at 16" and 50"- 54" from floor	Integrated light curtain	Integrated light curtain
Reversing safety edge	Wireless reversing edge; Flexible bottom bar with detachable bottom seal	Wireless reversing edge	Wireless reversing edge	Wireless reversing edge	Wireless reversing edge	Wireless reversing edge	Wireless reversing edge	Wireless reversing edge	Wireless reversing edge
Available supply voltages ³	120V AC 1PH, 208V AC 1PH ⁺ , 220V AC 1PH, 208V AC 3PH ⁺ , 230V AC 3PH, 460V AC 3PH, 575V AC 3PH [†] ('requires stand-alone mounted transformer)	120V AC 1PH, 208V AC 1PH [†] , 220V AC 1PH, 208V AC 3PH [†] , 230V AC 3PH, 460V AC 3PH, 575V AC 3PH [†] ('requires stand-alone mounted transformer)	120V AC 1PH, 208V AC 1PH [†] , 220V AC 1PH, 208V AC 3PH [†] , 230V AC 3PH, 460V AC 3PH, 575V AC 3PH [†] (¹requires stand-alone mounted transformer)	120V AC 1PH, 208V AC 1PH ⁺ , 220V AC 1PH, 208V AC 3PH ⁺ , 230V AC 3PH, 460V AC 3PH, 575V AC 3PH [†] ('requires stand-alone mounted transformer)	208V AC 3PH†, 230V AC 3PH, 460V AC 3PH, 575V AC 3PH† (*requires stand-alone mounted transformer)	208V AC 3PH†, 230V AC 3PH, 460V AC 3PH, 575V AC 3PH† (*requires stand-alone mounted transformer)	230V AC 3PH, 460V AC 3PH, 575V AC 3PH ¹ ('requires stand-alone mounted transformer)	230V AC 3PH, 460V AC 3PH, 575V AC 3PH ¹ ('requires stand-alone mounted transformer)	230V AC 3PH, 460V AC 3PH, 575V AC 3PH† (*requires stand-alone mounted transformer)
Hinged guides	Provide easy access for maintenance	Provide easy access for maintenance	N/A	N/A	Provide easy access for maintenance	Provide easy access for maintenance			
Warranty	5-Year Limited on drive motor and gearbox; 1-Year Limited on all other components	5-Year Limited	5-Year Limited	5-Year Limited	5-Year Limited	5-Year Limited	5-Year Limited	5-Year Limited	5-Year Limited
Curtain color options Actual colors may vary due to fluctuation in the printing process. Always request a color sample from your Overhead Door** Distributor for accurate color matching.									
	Red Blue White Gray Black Orange Yellow FDA White FDA Royal Blue (991 and 992 only) (991 and 992 only)			Gray Orange Above colors also available for Model 992 a	Red Blue s optional exterior/interior curtain material	Black Blue	ck Blue White Gray Red Blue Silver powder coat made Approximately 200 RAL powder coat to mimic anodized aluminum finishes available.		
Comments	² Wind load is the ultimate pressure tested at door width of 12'.	¹ Air tightness is independently tested to ASTM E283 test standard. ² Wind load is the ultimate pressure tested at door width of 10'	² Wind load is the ultimate pressure tested at door width of 16'.	² Wind load is the ultimate pressure tested at door width of 20'.	² Wind load is the ultimate pressure tested at door width of 20'.	² Wind load is the ultimate pressure tested at door width of 19'.	Wind load is the ultimate pressure tested at door width of 10'. Applications with air curtain may require	 Wind load is the ultimate pressure tested at door width of 15'. Up to 50.0 psf with optional vision panels. 	² Wind load is the ultimate pressure tested at door width of 15'.