

625

STORMTITE™



INSULATED HEAVY-DUTY ROLLING SERVICE DOOR



THERMAL PROTECTION.
HEAVY-DUTY DESIGN.
AIR INFILTRATION PROTECTION.



INDUSTRY LEADING
COMMERCIAL & INDUSTRIAL SOLUTIONS



Standard features at a glance

| | |
|-------------------|-------------------------------------------------------------------------------------------------|
| Max height | 28'4" (8636 mm) |
| Max width | 30'4" (9246 mm) |
| Curtain | 24-gauge galvanized steel front; 24-gauge galvanized steel back |
| Slat profile | Flat, insulated, type F-265i |
| Insulation | Foamed-in-place, CFC/HCFC-free polyurethane |
| R-value* | 7.7 (1.35 W/Msq) |
| STC rating | 21 |
| Finish | White, Tan, Gray or Brown |
| Hood | 24 ga. galvanized steel |
| Wind load | 20 psf |
| Standard mounting | Face-of-wall |
| Operation | Chain hoist |
| Standard springs | 20,000 cycle |
| Weatherseals | Bottom, exterior curtain-side guide, interior hood baffle |
| Guides | Three structural steel angles; PowderGuard® Premium finish with black powder coat |
| Bottom bar | Insulated double angle with vinyl weatherseal |
| Lock | Padlockable chain keeper |
| Warranty | 24-month limited; 3 years/20,000 cycle limited on Overhead Door™ door and operator system |

Options

- Electric operator (RHX®, RSX®, RMX®) or crank operation
- Bottom sensing edge
- Galvanized steel bottom bar angle and guides; insulated guides
- Sloping bottom bar
- Between-jamb mounting
- Stainless steel or aluminum slats
- High-usage package
- High-wind load option (FBC, TDI, DADE, HVHZ)†
- Weatherseal for interior side guide; Lintel seal
- Cylinder lock; Slide bolts; Exhaust ports
- Uniformly spaced vision lites of 5/8" x 3" (16 mm x 76 mm) or 1" x 10" (24.5 mm x 254 mm)
- PowderGuard® Premium powder coat paint finish in approximately 200 standard colors
- PowderGuard® Zinc and PowderGuard® Textured finishes
- Special application doors:
 - Oversized doors to 1500 sq. ft. (139.4 sq. m)
 - Combination doors with grilles and/or with full or partial standard, perforated or fenestrated slats
 - Spark-resistant doors, craneway doors, pass doors
- IECC listed air infiltration package (meets IECC code requirements 2012 C402.4.3/2015 C402.5.2); includes guide cover and cap; dual brush guide seal; lintel seal; bottom astragal

† Wind Load options available to meet:
FBC - Florida Building Code; TDI - Texas Department of Insurance;
DADE - Miami-Dade Building Code Compliance Office

* R-value is a measure of thermal efficiency. The higher the R-value the greater the insulating properties of the door. Overhead Door Corporation uses a calculated door section R-value for our insulated doors.

Cover image: Model 625, finish in Tan

Image above: Model 625, finish in Tan



Style, function and thermal efficiency.

When overall performance and thermal efficiency are as essential in a rolling service door as are versatile good looks, the Stormtite™ 625 meets specification and exceeds all expectations. This heavy-duty door features insulated slats in a variety of materials – galvanized steel, stainless steel or aluminum – and offers optional wind load protection up to 170 psf. Designed to fit openings up to 30'4" wide and 28'4" high (9246 mm x 8636 mm) and offered with a broad range of product options, the versatility and functionality of the Stormtite™ 625 ensures that your design requirements will be met with ease, functionality and style.




White finish. Installation and service: Overhead Door Company of Concord

Slat data

F-265i slat

| Slat | Opening width | Standard | Optional |
|-------|----------------------|----------|--------------------------------------------------------|
| F265i | Thru 30'4" (9246 mm) | 24 ga. | 22, 20, 18 ga. 22, 20 ga. ss .040" alum., 18 ga. |

Slats are galvanized and painted, stainless steel (specify finish) or aluminum (specify finish). Gauges reflect front slat; back slat is 24-gauge on steel and stainless steel; 22-gauge on aluminum.



R-value* 7.7 (1.35 W/Msq)
U-value .13
Smoke generation = 10
Flame spread = 5
STC = 21



The IECC listed air infiltration option meets code requirements for an air infiltration rating lower than than 1.0 cfm/ft² for rolling steel doors.

This superior perimeter sealing system includes:

- Guide cover and cap
- Dual brush guide seal
- Lintel seal
- Bottom astragal


Finish options

| | Finish details |
|----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| Standard polyester base coat | Two-coat system with polyester based top coat. |
| PowderGuard® Premium powder coat | Weather resistant polyester powder coat available in approximately 200 colors; custom color match and EZ Clean treatment options available. |
| PowderGuard® Zinc finish | Zinc enriched powder coat provides excellent corrosion protection that outperforms both hot dipped and cold galvanized steel. Color selection from approximately 200 powder coat colors; custom color match also available. |
| PowderGuard® Textured finish | Industrial textured powder coat provides a thicker, more scratch resistant coat for added product protection. |

Colors



White



Tan



Gray



Brown

Actual colors may vary from brochure due to fluctuations in the printing process. Always request a color sample from your Overhead Door™ Distributor for accurate color matching.



Gray finish. Installation and service: Overhead Door Company of Huntsville



Architect's Corner

A resource for architects, containing comprehensive technical and resource materials to support your project, including drawings and specifications for commercial doors.

www.overhaddoor.com

The original, innovative choice for unequalled quality and service.

Overhead Door pioneered the upward-acting door industry, inventing the first upward-acting door in 1921 and the first electric door operator in 1926. Today, we continue to be the industry leader through the strength of our product innovation, superior craftsmanship and outstanding customer support, underscoring a legacy of quality, expertise and integrity. That's why design and construction professionals specify Overhead Door products more often than any other brand. Our family of over 400 Overhead Door Distributors across the U.S. and Canada not only share our name and logo, but also our commitment to excellence.



INDUSTRY LEADING
COMMERCIAL & INDUSTRIAL SOLUTIONS



2501 S. State Hwy. 121 Bus., Suite 200, Lewisville, TX 75067
1-800-929-DOOR • sales@overhaddoor.com
www.overhaddoor.com